

O₂

OXY-4 micro & OXY-10 micro

Multi-channel oxygen transmitters

Parallel monitoring of up to 10 sensors


- For use with oxygen microsensors
- Compact design
- Software included

The OXY-4 micro and OXY-10 micro are precise multi-channel oxygen meters. They are used with oxygen microsensors based on a 140 μm optical fiber. A PC is connected to run the easy-to-use software. OXY-4 micro and OXY-10 micro are used for microsensors type PSt1 (detection limit 20 ppb, 0-50 % oxygen).




Specifications	OXY-4 micro	OXY-10 micro
Oxygen sensors	PSt1 only (optical STconnector)	
Power supply	110 - 230 VAC, 50/60 Hz, max. 40VA (cables included)	
Temperature: operating / storage	0°C to +50 °C / -10°C to 60°C	
Relative humidity	up to 80 % (non condensing)	
Dimensions	300 mm x 250 mm x 135 mm	
Weight	3,3 kg	3,9 kg
Digital interface	RS 232 interface (with RJ connector to serial port, cable included)	
Software OxyView (included)	Windows 98, 2000, XP	

Sensors & Accessories



Needle-type oxygen microsensors

This oxygen microsensor is protected by its robust housing.



Implantable oxygen microsensors

This oxygen microsensor offers the probe without any additional housing.



Flow-through cell housed oxygen microsensor

This sensor is integrated in a T-shaped cell.



Flow-through cell metal housing oxygen microsensor

Provides a gas tight & small measurement cell.

A wide variety of sensors is offered.
If your housing is missing,
please contact us!

Technical data can change without prior notice.

Bring to light what's inside. Ask our experts:

PreSens Precision Sensing GmbH
Josef-Engert-Str. 11
93053 Regensburg, Germany

Phone +49 941 94272100
Fax +49 941 94272111
info@PreSens.de

 www.PreSens.de